

TECHNICAL DATA

Scapa 3160

Waterproof Cloth Tape

DESCRIPTION

Scapa 3160 is a standard grade, polyethylene laminated, waterproof cloth tape, coated with a pressure sensitive adhesive

Scapa 3160 is available in black, white and silver.

APPLICATIONS

- Designed as a general purpose waterproof cloth tape
- Used for sealing, bundling, short term masking and protecting
- Excellent for jointing polyethylene sheeting in asbestos removal applications
- Double glazing unit sealing
- Medium temperature duct sealing within HVAC
- Carpet joining and edging

PRODUCT BENEFITS

- Good water resistance
- Excellent adhesion and strength
- Flexible and conformable
- Easy tear
- Good low temperature performance
- Good all purpose product
- Service Temperature -10 to +75°C

Issue : 8 Date : 010/02/2014 Page 1 of 2 3160.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, it analy circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.155	AFERA 5006*
Tensile Strength	N/cm	35	IEC 454-2
Adhesion to Steel	N/cm	5	IEC 454-2
Adhesion to Backing	N/cm	3	IEC 454-2

^{*}Scapa Internal Test Method to measure thickness now replaced by the more rigorous AFERA method.

STANDARD PRESENTATION

Roll Length: 25m, 50m

• Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

Core: Cardboard

Packaging: Bulk packed using interleaving sheets between layers./Shrink wrapped in packs of 4 *

Note: Information on stock items, non-standard sizes and colours, and lead times is available on request *Dependant on size/colour combination

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.

Issue: 8 Date: -10/02/2014 Page 2 of 2 3160.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.